



new witness made at the N.W. corner
Section 34 T. 7. R. 1. E. Maple 9 S 42° E 31

A corner 80 poles 6 1/4 links east of N.W.
corner of Sec 34 T. 7. R. 1. East Limestone
Witnessed by Black Oak 7 N 54 1/2° E 19
Gum 24 N 61° W 21 1/2.

B Northern 1/2 mile post Sand Stone
Witnessed by Red Oak 3 S 82° W 12
Hickory 12 N 13 1/2° E 29

C corner halfway between
western half mile stake and center
of Section Sand Stone
Witnessed by W Oak 24 S 61 1/2° W 16
Black Oak 7 N 9° W 32

D corner at center of section Sand Stone
Witnessed by W Oak 40 S 65° E 45
Hickory 3 N 33° E 21 1/2

E corner halfway between N 1/2 mile stone
and center of section Sand Stone
Witnessed by Chestnut 1 N 41 1/2° W 23 1/2
Apple Tree 3 S 86 1/2° E 78

F corner halfway between N.E.
corner and E 1/2 M.S. Sand Stone
Witnessed by Ash 7 S 89° E 18
Hickory 10 N 33° W 19

G corner halfway between E 1/2 P Sand Stone
Witnessed by Hickory 9 S 33° W 19
Chestnut 10 S 54° E 58

H corner halfway between
Eastern 1/2 mile and center of
section Sand Stone
Witnessed by B. Oak 3 S 87° E 51
Red Oak 8 N 35° W 19

Martin Deekard } chain bearers
George Seips } sworn

A. J. Helenburg } flag bearer sworn

H. W. Buschick
Surveyor Monroe County